



This is a 6.0 mil flexible matte white vinyl film coated with a removable pressure sensitive acrylic adhesive and backed with a 2-sided poly coated 90# stay flat liner

CAUTION: DIGITAL PRINTS MUST BE ALLOWED TO CURE 24-48 HOURS BEFORE LAMINATING OR APPLICATION. WE HIGHLY RECOMMEND LEAVING A ½ INCH UNPRINTED BORDER AROUND THE GRAPHIC.

Printer/Ink compatibility	Solvent, Eco Solvent, UV Curable, Latex and Screen Print	
THICKNESS	Film-6.0 mil, Adhesive .8-1. mil, Liner 6.7mil +/- %10	ASTM D 3652
REMOVABILITY	With in 1 Year	Under normal interior conditions
WATER RESISTANCE	Limited	
SHELF LIFE	6 months at 70°	At %50 humidity
SERVICE TEMP RANGE	-40° to 200° F	
MINIMUM APPLICATION	40° F (10°C)	
TACK	430	ASTM D 2979

Designed for temporary application of decals and graphics to most types of painted interior walls and windows to most flat, semi-gloss and gloss paint finishes. Painted wall need to be fully cured (90 days). Decals may also be applied to sealed wall coverings. The surface must be smooth and clean prior to application. Please read Print and Installation bulletin before starting a job.