

### Product Specification Sheet

## AMGBacklit8 Backlit Front Glossy

### PRODUCT OVERVIEW

Translucent polyester backlit film with specialized water-resistant coating

Ultra white glossy finish and durable PET base

Sharp image reproductions that stand out with the light on or off

Ideal for backlit film applications and compatible with both dye & UV pigmented based aqueous inks

### PRODUCT SUGGESTED APPLICATION

Light box advertising (graphic in the panel)

Illuminated displays

Backlit tradeshow and exhibition

Signage/banner

Department store display

### PRODUCT SPECIFICATIONS

Caliper:	215 microns (8.6 mil)	Inks:	Aqueous (inkjet) / Dye
Weight:	285g	Width:	36" / 42" / 50" / 60"
Base material:	Polyester film	Length:	30m (100 ft)
Surface:	High Glossy	Core:	3"

### PRINTING TIPS

Suitable printing condition: Temperature 15~30°C (59~86°F) / Humidity 30~60% Recommended pre and post heater settings are around 30°C(86°F). Lamination is optional. In order to protect the image from physical damage and to decrease image fading, overlaminates is recommended. Storage: It is recommended to store in the closed original packing in a cool and dry environment. Temperature 10°~25°C (50°~77°F), Relative Humidity 50%. Shelf Life: One year stored in original package in recommended condition.

### ASSISTANCE

Call us at 908-686-2200 or visit [www.ddpmc.com](http://www.ddpmc.com)

### Product Specification Sheet

## AMGPhoto8 M/P Premium Glossy Photo Paper 200

### PRODUCT OVERVIEW

Professional glossy long lasting prints and color stability

Excellent solution for quality conscious graphic designers and professional photographers

Proprietary microporous coating and opaque double sided true resin coated paper base

Achieve the color and print reproduction desired with an exceptionally fast dry time

### PRODUCT SUGGESTED APPLICATION

Photo realistic prints, albums & frames

Posters

Billboards

Digital camera images

CD booklets

Indoor/outdoor posters & signage

Shop display

Exhibits

### PRODUCT SPECIFICATIONS

Caliper: 186 microns (7.4 mil)

Weight: 191g

Base material: RCP

Surface: High Glossy

Inks: Aqueous (inkjet) / Dye / Latex

Width: 24" / 36" / 42" / 44" / 50" / 60"

Length: 30m (100 ft)

Core: 3"

### PRINTING TIPS

Dry time will vary depending on ink type. Dry time will vary depending on ink type. Lamination is optional. In order to protect the image from physical damage and to decrease image-fading, overlaminates are recommended. Storage: It is recommended to store in the closed original packing in a cool and dry environment Temperature 10°~25°C (50°~77°F), Relative Humidity 50%. Shelf Life: One year stored in original package in recommended condition.

### ASSISTANCE

Call us at 908-686-2200 or visit [www.ddpmc.com](http://www.ddpmc.com)



**B.C.I.**  
IMAGING

[www.bciimage.com](http://www.bciimage.com)

866 971-1008

### Product Specification Sheet

## AGPhoto8-PSA M/P Premium Adhesive Glossy Photo Paper 200

### PRODUCT OVERVIEW

Professional glossy long lasting prints and color stability

Excellent solution for quality conscious graphic designers and professional photographers alike

Proprietary microporous coating and opaque double sided true resin coated paper base

Exceptionally fast dry time

### PRODUCT SUGGESTED APPLICATION

Photo realistic prints, albums & frames

Posters

Billboards

Digital camera images

CD booklets

Indoor/outdoor posters & signage

Shop display

Exhibit

### PRINTING TIPS

Caliper:	259 microns (10.4 mil)	Inks:	Aqueous (inkjet) / Dye
Weight:	280g (200g w/o adhesive)	Width:	36" / 42" / 50" / 60"
Base material:	RCP	Length:	30m (100 ft)
Surface:	High Gloss	Core:	3"

### PRINTING TIPS

Dry time will vary depending on ink type. Dry time will vary depending on ink type. Lamination is optional. In order to protect the image from physical damage and to decrease image-fading, overlaminates are recommended. Storage: It is recommended to store in the closed original packing in a cool and dry environment Temperature 10°~25°C (50°~77°F), Relative Humidity 50%. Shelf Life: One year stored in original package in recommended condition.

## AMGPhoto10 M/P Premium Glossy Photo Paper 250

### PRODUCT OVERVIEW

Professional glossy long lasting prints and color stability

Excellent solution for quality conscious graphic designers and professional photographers alike

Proprietary microporous coating and opaque double sided true resin coated paper base

Achieve the color and print reproduction desired with an exceptionally fast dry time

### PRODUCT SUGGESTED APPLICATION

Photo realistic prints, albums & frames

Posters

Billboards

Digital camera images

CD booklets

Indoor/outdoor posters & signage

Shop display

Exhibit

### PRODUCT SPECIFICATIONS

Caliper: 236 microns (9.4 mil)

Weight: 241g

Base material: RCP

Surface: High Glossy

Inks: Aqueous (inkjet) / Dye / Latex

Width: 24" / 36" / 42" / 44" / 50" / 60"

Length: 30m (100 ft)

Core: 3"

### PRINTING TIPS

Dry time will vary depending on ink type. Lamination is optional. In order to protect the image from physical damage and to decrease image fading, overlaminates is recommended. Storage: It is recommended to store in the closed original packing in a cool and dry environment. Temperature 10°~25°C (50°~77°F), Relative Humidity 50%. Shelf Life: One year stored in original package in recommended condition.



**B.C.I.**  
IMAGING

[www.bciimage.com](http://www.bciimage.com)

866 971-1008

### Product Specification Sheet

## AMGPoly9-PSA M/P Self Adhesive Polypropylene Glossy

### PRODUCT OVERVIEW

M/P coated glossy self adhesive polypropylene  
Curl free and water resistant  
Sharp color expression - indoor and outdoor applications

### PRODUCT SUGGESTED APPLICATION

Posters  
Rollup displays  
POS printing  
Indoor and outdoor banners  
Retail aisle banners  
Tradeshow panels  
Exhibition graphics  
Instruction plates

### PRODUCT SPECIFICATIONS

Caliper:	228 microns (9.1 mil)	Inks:	Aqueous (inkjet) / Dye
Weight:	210g	Width:	24" / 36" / 42" / 50" / 60"
Base material:	PP	Length:	30m (100 ft)
Surface:	Glossy	Core:	3"

### PRINTING TIPS

Suitable printing condition: Temperature 15~30°C (59~86°F) / Humidity 30~60% Recommended pre and post heater settings are around 30°C(86°F). Lamination is optional. In order to protect the image from physical damage and to decrease image fading, overlaminates is recommended. Storage: It is recommended to store in the closed original packing in a cool and dry environment. Temperature 10°~25°C (50°~77°F), Relative Humidity 50%. Shelf Life: One year stored in original package in recommended condition.

### ASSISTANCE

Call us at 908-968-2200 or visit [www.ddpmsc.com](http://www.ddpmsc.com)

## Product Specification Sheet

# AMGRoll-up6 M/P White PET Gray Backed Rollup Film

## PRODUCT OVERVIEW

Instant dry coating that is compatible with dye & UV pigmented based aqueous inks

Dimensionally stable product that will not buckle, warp, or curl

High quality pure white PET film with blockout capable of reproducing photo quality images

## PRODUCT SUGGESTED APPLICATION

Indoor and outdoor banners

Posters & billboards

POS printing

Rollup displays

Retail aisle banners

Tradeshow panels

Instruction plates

## PRODUCT SPECIFICATIONS

Caliper:	160 microns (6.4 mil)	Inks:	Aqueous (inkjet) / Dye
Weight:	227g	Width:	36" / 50" / 60"
Base material:	White PET	Length:	30m (100 ft)
Surface:	Glossy	Core:	3"

## PRINTING TIPS

Suitable printing condition: Temperature 15~30°C (59~86°F) / Humidity 30~60% Recommended pre and post heater settings are around 30°C(86°F). Lamination is optional. In order to protect the image from physical damage and to decrease image fading, overlaminates is recommended. Storage: It is recommended to store in the closed original packing in a cool and dry environment. Temperature 10°~25°C (50°~77°F), Relative Humidity 50%. Shelf Life: One year stored in original package in recommended condition.

## ASSISTANCE

Call us at 908-686-2200 or visit [www.ddpmc.com](http://www.ddpmc.com)

**B.C.I.**  
IMAGING[www.bciimage.com](http://www.bciimage.com)

866 971-1008

## AMMBacklit8 Backlit Front Matte 215

### PRODUCT OVERVIEW

Translucent polyester backlit film with specialized water-resistant coating  
Ultra white finish with durable PET base  
Sharp image reproductions with light on or off  
Ideal for all backlit film applications  
Compatible with both dye & UV pigmented aqueous based inks

**Certified for  
HP Latex Inks**

### PRODUCT SUGGESTED APPLICATION

Light box advertising  
Illuminated displays  
Tradeshow and exhibition graphics  
Signage

All retail advertisement applications  
Cosmetics  
Fashion imaging  
Airport and transit

### PRODUCT SPECIFICATIONS

Caliper: 215 microns (8.6 mil)  
Weight: 270g  
Base material: PET  
Surface: Matte

Inks: Aqueous (inkjet) / Dye / Latex  
Width: 36" / 42" / 50" / 60"  
Length: 36m (100 ft)  
Core: 3"

### PRINTING TIPS

Suitable printing condition: Temperature 15~30°C (59~86°F) / Humidity 30~60% Recommended pre and post heater settings are around 30°C (86°F). Lamination is optional. In order to protect the image from physical damage and to decrease image fading, overlaminates is recommended. Storage: It is recommended to store in the closed original packing in a cool and dry environment. Temperature 10°~25°C (50°~77°F), Relative Humidity 50%. Shelf Life: One year stored in original package in recommended condition.

### ASSISTANCE

Call us at 908-686-2200 or visit [www.ddpmsc.com](http://www.ddpmsc.com)



**B.C.I.**  
IMAGING

[www.bciimage.com](http://www.bciimage.com)

866 971-1008

### Product Specification Sheet

## AMMPoly7-PSA Self Adhesive Polypropylene Matte

### PRODUCT OVERVIEW

Asymmetrically coated matte, self-adhesive polypropylene film  
Curl-free, waterfast and scratch resistant properties  
Economical - perfect for short-term applications where price is key  
Compatible with both dye & UV pigmented aqueous ink jet printers  
Offers a high image definition - PVC free

### PRODUCT SUGGESTED APPLICATION

Indoor/outdoor use  
POP/POS displays  
Tradeshow displays  
Instruction plates  
Posters  
Graphics

### PRODUCT SPECIFICATIONS

Caliper:	185 microns (7.4 mil)	Inks:	Aqueous (inkjet) / Dye
Weight:	175g	Width:	24" / 36" / 42" / 50" / 60"
Base material:	PP	Length:	30m (100 ft)
Surface:	Matte	Core:	3"

### PRINTING TIPS

Suitable printing condition: Temperature 15~30°C (59~86°F) / Humidity 30~60% Recommended pre and post heater settings are around 30°C(86°F). Lamination is optional. In order to protect the image from physical damage and to decrease image fading, overlaminates is recommended. Storage: It is recommended to store in the closed original packing in a cool and dry environment. Temperature 10°~25°C (50°~77°F), Relative Humidity 50%. Shelf Life: One year stored in original package in recommended condition.



### Product Specification Sheet

## AMMPolyBanner8 W/R Polypropylene Banner Matte

### PRODUCT OVERVIEW

Economical 8 mil. polypropylene durable banner with water and UV resistant properties

Provides a high quality image with a matte finish - reduces glare from indoor lighting

Water resistant coating with an ultra white matte surface

Compatible with both dye & UV pigmented aqueous based inks

### PRODUCT SUGGESTED APPLICATION

Photo realistic prints, albums & frames

Posters

Billboards

Digital camera images

CD booklets

Indoor POP

Shop display

Exhibit

### PRODUCT SPECIFICATIONS

Caliper: 205 microns (8.2 mil)

Weight: 130g

Base material: Paper

Surface: Matte

Inks: Aqueous (inkjet) / Dye

Width: 24" / 36" / 42" / 44" / 50" / 60"

Length: 30m (100 ft)

Core: 3"

### PRINTING TIPS

Dry time will vary depending on ink type. Dry time will vary depending on ink type. Lamination is optional. In order to protect the image from physical damage and to decrease image-fading, overlaminates are recommended. Storage: It is recommended to store in the closed original packing in a cool and dry environment Temperature 10°~25°C (50°~77°F), Relative Humidity 50%. Shelf Life: One year stored in original package in recommended condition.

### Product Specification Sheet

## AMMPvc Self Adhesive Vinyl Matte

### PRODUCT OVERVIEW

Economical and permanent self-adhesive matte PVC vinyl film

Curl free, waterfast and scratch resistant

Intended for use in both dye & UV pigmented ink aqueous based printers

High image definition material and excellent durability at a great price

### PRODUCT SUGGESTED APPLICATION

Indoor/outdoor use

POP/POS displays

Instruction plates

Posters

Graphics

### PRODUCT SPECIFICATIONS

Caliper: 225 microns (9.0 mil)

Weight: 275g

Base material: PVC

Surface: Matte

Inks: Aqueous (inkjet) / Dye

Width: 24" / 36" / 42" / 50" / 60"

Length: 30m (100 ft)

Core: 3"

### PRINTING TIPS

Suitable printing condition: Temperature 15~30°C (59~86°F) / Humidity 30~60% Recommended pre and post heater settings are around 30°C(86°F). Lamination is optional. In order to protect the image from physical damage and to decrease image fading, overlaminates is recommended. Storage: It is recommended to store in the closed original packing in a cool and dry environment. Temperature 10°~25°C (50°~77°F), Relative Humidity 50%. Shelf Life: One year stored in original package in recommended condition.

### ASSISTANCE

Call us at 908-686-2200 or visit [DDPMSC.com](http://DDPMSC.com)



**B.C.I.**  
IMAGING

[www.bciimage.com](http://www.bciimage.com)

866 971-1008

### Product Specification Sheet

## AMMRoll-up5 Rollup Banner Matte

### PRODUCT OVERVIEW

Photo quality pure white PET film with blackout

Matte film - water resistant coating with ultra white surface

Anti-curl and anti-glare reduces reflections on printed surface

Perfect for promotional rollups, posters, and tradeshow graphics

### PRODUCT SUGGESTED APPLICATION

Indoor and outdoor banners

Posters & billboards

POS printing

Rollup displays

Retail aisle banners

Tradeshow panels

Instruction plates

### PRODUCT SPECIFICATIONS

Caliper:	135 microns (5.4 mil)	Inks:	Aqueous (inkjet) / Dye
Weight:	175g	Width:	36" / 50" / 60"
Base material:	White PET	Length:	30m (100 ft)
Surface:	Matte	Core:	3"

### PRINTING TIPS

Suitable printing condition: Temperature 15~30°C (59~86°F) / Humidity 30~60% Recommended pre and post heater settings are around 30°C(86°F). Lamination is optional. In order to protect the image from physical damage and to decrease image fading, overlaminates is recommended. Storage: It is recommended to store in the closed original packing in a cool and dry environment. Temperature 10°~25°C (50°~77°F), Relative Humidity 50%. Shelf Life: One year stored in original package in recommended condition.



**B.C.I.**  
IMAGING

[www.bciimage.com](http://www.bciimage.com)

866 971-1008

### Product Specification Sheet

## AMMRoll-up10 Blockout Tradeshow /Rollup PET/PP Film

### PRODUCT OVERVIEW

10 mil anti curl, multi-layered PET/PP film

Non-transmissive blockout for brilliant full color prints

Tear and fade resistant that will withstand all application conditions

### PRODUCT SUGGESTED APPLICATION

Indoor and outdoor banners

Posters & billboards

POS printing

Retail aisle banners

Tradeshow panels

Instruction plates

### PRODUCT SPECIFICATIONS

Caliper:	250 microns (10 mil)	Inks:	Aqueous (inkjet) / Dye
Weight:	215g	Width:	36" / 50" / 60"
Base material:	PET & PP	Length:	30m (100 ft)
Surface:	Matte	Core:	3"

### PRINTING TIPS

Suitable printing condition: Temperature 15~30°C (59~86°F) / Humidity 30~60% Recommended pre and post heater settings are around 30°C(86°F). Lamination is optional. In order to protect the image from physical damage and to decrease image fading, overlaminates is recommended. Storage: It is recommended to store in the closed original packing in a cool and dry environment. Temperature 10°~25°C (50°~77°F), Relative Humidity 50%. Shelf Life: One year stored in original package in recommended condition.

### ASSISTANCE

Call us at 800-240-9455 or visit McGrannDigital.com

**Product Specification Sheet**

## AMMRoll-up14 Gray Backed Tradeshow PET/PP Film

### PRODUCT OVERVIEW

14 mil anti curl, multi-layered PET/PP gray backed blackout film

Non-transmissive blackout and matte coating allows for brilliant full color prints

Tear & fade resistant material that withstands all applications both indoor and outdoor

### PRODUCT SUGGESTED APPLICATION

Pop-up displays

POS printing

Indoor and outdoor banners

Retail aisle banners

Tradeshow

Exhibition graphics

Instruction plates

### PRODUCT SPECIFICATIONS

Caliper: 350 microns (14 mil)

Weight: 410g

Base material: PET & PP

Surface: Matte

Inks: Aqueous (inkjet) / Dye

Width: 36" / 50" / 60"

Length: 30m (100 ft)

Core: 3"

### PRINTING TIPS

Suitable printing condition: Temperature 15~30°C (59~86°F) / Humidity 30~60% Recommended pre and post heater settings are around 30°C(86°F). Lamination is optional. In order to protect the image from physical damage and to decrease image fading, overlaminates is recommended. Storage: It is recommended to store in the closed original packing in a cool and dry environment. Temperature 10°~25°C (50°~77°F), Relative Humidity 50%. Shelf Life: One year stored in original package in recommended condition.

### ASSISTANCE

Call us at 908-686-2200 or visit [www.ddpmsc.com](http://www.ddpmsc.com)

### Product Specification Sheet

## AMMScrim10 Super Smooth Aqueous Scrim Vinyl

### PRODUCT OVERVIEW

Extremely smooth surface

Universal aqueous vinyl banner - tear resistant fabric, blockout and vinyl layers

Matte, waterfast coating that allows for high image quality resolution and vibrant color reproduction

### PRODUCT SUGGESTED APPLICATION

POS printing

Rollup banner stands

Tradeshow graphics

Hanging banners

### PRODUCT SPECIFICATIONS

Caliper:	295 microns (11.6 mil)	Inks:	Aqueous (inkjet) / Dye
Weight:	375g	Width:	24" / 36" / 42" / 50" / 60"
Base material:	Tarpaulin	Length:	20m (65 ft)
Surface:	Matte	Core:	3"

### PRINTING TIPS

Suitable printing condition: Temperature 15~30°C (59~86°F) / Humidity 30~60% Recommended pre and post heater settings are around 30°C(86°F). Lamination is optional. In order to protect the image from physical damage and to decrease image fading, overlaminates is recommended. Storage: It is recommended to store in the closed original packing in a cool and dry environment. Temperature 10°~25°C (50°~77°F), Relative Humidity 50%. Shelf Life: One year stored in original package in recommended condition.

### ASSISTANCE

Call us at 908-686-2200 or visit [www.ddpmsc.com](http://www.ddpmsc.com)



**B.C.I.**  
IMAGING

[www.bciimage.com](http://www.bciimage.com)

866 971-1008

### Product Specification Sheet

## AMMWallFab13 Easy-Tex Self Adhesive Fabric

### PRODUCT OVERVIEW

Sticks to any non-porous flat surface

Removable, reusable, repositionable and removes easily with no residue

Sharp-looking, seamless graphics and superior photographic images every time

Ideal for life size photographic cut-outs for walls and wall murals

Indoor and outdoor applications, including windows, backlits, doors, sign boards, and other flat surfaces

Applies without wrinkles and does not tear

### PRODUCT SUGGESTED APPLICATION

Posters

POS/POP printing

Indoor and outdoor banners

Tradeshows panels

Exhibition graphics

Instruction plates

### PRODUCT SPECIFICATIONS

Caliper: 335 microns (13.4 mil)

Weight: 305g

Base material: 100% Polyester Woven Fabric

Surface: Matte

Inks: Aqueous (inkjet) / Dye

Width: 24" / 36" / 42" / 60"

Length: 30m (100 ft)

Core: 3"

### PRINTING TIPS

Suitable printing condition: Temperature 15~30°C (59~86°F) / Humidity 30~60% Recommended pre and post heater settings are around 30°C(86°F). Lamination is optional. In order to protect the image from physical damage and to decrease image fading, overlaminates is recommended. Storage: It is recommended to store in the closed original packing in a cool and dry environment. Temperature 10°~25°C (50°~77°F), Relative Humidity 50%. Shelf Life: One year stored in original package in recommended condition.



**B.C.I.**  
IMAGING

[www.bciimage.com](http://www.bciimage.com)

866 971-1008

### Product Specification Sheet

## AMSPHOTO8 M/P Premium Satin Photo Paper 200

### PRODUCT OVERVIEW

Professional satin long lasting prints and color stability

Excellent solution for quality conscious graphic designers and professional photographers

Proprietary microporous coating and opaque double sided true resin coated paper base

Exceptionally fast dry time

### PRODUCT SUGGESTED APPLICATION

Photo realistic prints, albums & frames

Posters

Billboards

Digital camera images

CD booklets

Indoor/outdoor posters & signage

Shop display

Exhibit

### PRODUCT SPECIFICATIONS

Caliper: 192 microns (7.7 mil)

Weight: 191g

Base material: RCP

Surface: Satin

Inks: Aqueous (inkjet) / Dye / Latex

Width: 24" / 36" / 42" / 50" / 60"

Length: 30m (100 ft)

Core: 3"

### PRINTING TIPS

Dry time will vary depending on ink type. Dry time will vary depending on ink type. Lamination is optional. In order to protect the image from physical damage and to decrease image-fading, overlaminates are recommended. Storage: It is recommended to store in the closed original packing in a cool and dry environment Temperature 10°~25°C (50°~77°F), Relative Humidity 50%. Shelf Life: One year stored in original package in recommended condition.



**B.C.I.**  
IMAGING

[www.bciimage.com](http://www.bciimage.com)

866 971-1008



### Product Specification Sheet

## AMSPhoto8-PSA M/P Premium Adhesive Satin Photo Paper 200

### PRODUCT OVERVIEW

Professional glossy long lasting prints and color stability

Excellent solution for quality conscious graphic designers and professional photographers alike

Proprietary microporous coating and opaque double sided true resin coated paper base

Exceptionally fast dry time

### PRODUCT SUGGESTED APPLICATION

Photo realistic prints, albums & frames

Posters

Billboards

Digital camera images

CD booklets

Indoor/outdoor posters & signage

Shop display

Exhibit

### PRINTING TIPS

Caliper:	265 microns (10.6 mil)	Inks:	Aqueous (inkjet) / Dye
Weight:	280g (200g w/o adhesive)	Width:	36" / 42" / 50" / 60"
Base material:	RCP	Length:	30m (100 ft)
Surface:	Satin	Core:	3"

### PRINTING TIPS

Dry time will vary depending on ink type. Dry time will vary depending on ink type. Lamination is optional. In order to protect the image from physical damage and to decrease image-fading, overlaminates are recommended. Storage: It is recommended to store in the closed original packing in a cool and dry environment Temperature 10°~25°C (50°~77°F), Relative Humidity 50%. Shelf Life: One year stored in original package in recommended condition.



**B.C.I.**  
IMAGING

[www.bciimage.com](http://www.bciimage.com)

866 971-1008

### Product Specification Sheet

## AMSPhoto10 M/P Premium Satin Photo Paper 250

### PRODUCT OVERVIEW

Professional satin long lasting prints and color stability

Excellent solution for quality conscious graphic designers and professional photographers alike

Proprietary microporous coating and opaque double sided true resin coated paper base

Achieve the color and print reproduction desired with an exceptionally fast dry time

### PRODUCT SUGGESTED APPLICATION

Photo realistic prints, albums & frames

Posters

Billboards

Digital camera images

CD booklets

Indoor/outdoor posters & signage

Shop display

Exhibit

### PRODUCT SPECIFICATIONS

Caliper: 241 microns (9.6 mil)

Weight: 241g

Base material: RCP

Surface: Satin

Inks: Aqueous (inkjet) / Dye / Latex

Width: 24" / 36" / 42" / 44" / 50" / 60"

Length: 30m (100 ft)

Core: 3"

### PRINTING TIPS

Dry time will vary depending on ink type. Dry time will vary depending on ink type. Lamination is optional. In order to protect the image from physical damage and to decrease image-fading, overlaminates are recommended. Storage: It is recommended to store in the closed original packing in a cool and dry environment Temperature 10°~25°C (50°~77°F), Relative Humidity 50%. Shelf Life: One year stored in original package in recommended condition.

### ASSISTANCE

Call us at 908-686-2200 or visit [www.ddpmc.com](http://www.ddpmc.com)



**B.C.I.**  
IMAGING

[www.bciimage.com](http://www.bciimage.com)

866 971-1008

### Product Specification Sheet

## SMGBacklit8 Premium Solvent Backlit Film Glossy

### PRODUCT OVERVIEW

Specialized coating for eco-solvent inks as well as brilliant color reproductions in light box applications with or without light

Glossy finish and advanced light diffusion coating provides the highest possible image resolution and color density

Best choice for true photo quality backlit images which rival those from lambda or light jet technology

### PRODUCT SUGGESTED APPLICATION

Light box graphic

Backlit tradeshow display

Department store display

Luminous advertising

Bus shelter & Metro illuminated signage

### PRODUCT SPECIFICATIONS

Caliper: 205 microns (8.2 mil)

Weight: 285g

Base material: PET

Surface: High Gloss

Inks: Eco-Solvent / Solvent / Latex / UV-Cure

Width: 36" / 54" / 60"

Length: 30m (100 ft)

Core: 3"

### PRINTING TIPS

Dry time will vary depending on ink type. Lamination is optional. In order to protect the image from physical damage and to decrease image-fading, overlaminates are recommended. Storage: It is recommended to store in the closed original packing in a cool and dry environment Temperature 10°~25°C (50°~77°F), Relative Humidity 50%. Shelf Life: One year stored in original package in recommended condition.

### ASSISTANCE

Call us at 908-686-2200 or visit [DDPMSC.com](http://DDPMSC.com)

## Product Specification Sheet

# SMGClearFilm6 Clear Polyester Film Glossy

### PRODUCT OVERVIEW

5 mil eco-solvent, solvent and UV cure clear PET film  
High ink load capabilities with scratch resistant properties  
Anti curl and static treated

### PRODUCT SUGGESTED APPLICATION

Posters  
Window Display  
POS printing  
GIS / Mapping

### PRODUCT SPECIFICATIONS

Caliper:	125 microns (5 mil)	Inks:	Eco-Solvent / Solvent / Latex / UV-Cure
Weight:	160g	Width:	36" / 54" / 60"
Base material:	PP	Length:	30m (100 ft)
Surface:	Glossy	Core:	3"

### PRINTING TIPS

Suitable printing condition: Temperature 15~30°C (59~86°F) / Humidity 30~60% Recommended pre and post heater settings are around 30°C (86°F). Lamination is optional. In order to protect the image from physical damage and to decrease image fading, overlaminates is recommended. Storage: It is recommended to store in the closed original packing in a cool and dry environment. Temperature 10°~25°C (50°~77°F), Relative Humidity 50%. Shelf Life: One year stored in original package in recommended condition.

### ASSISTANCE

Call us at 908-6862200 or visit [DDPMSC.com](http://DDPMSC.com)

### Product Specification Sheet

## SMGPhoto8 Solvent Photo Paper Glossy

### PRODUCT OVERVIEW

Specialized coating for eco-solvent inks

Long lasting durability for both indoor and outdoor applications

Provides cost effective solution by using a multipurpose base with our advanced IJ receptive coating for photo quality prints.

### PRODUCT SUGGESTED APPLICATION

Indoor and outdoor

Photo realistic prints

Fine art reproduction

Displays: posters, billboards, kiosks

Latex printing media (new printer application)

### PRODUCT SPECIFICATIONS

Caliper: 192 microns (7.8 mil)

Weight: 230g

Base material: Paper

Finish: Glossy

Inks: Eco-Solvent / Solvent / Latex / UV-Cure

Width: 36" / 54" / 60"

Length: 50m (165 ft)

Core: 3"

### PRINTING TIPS

Suitable printing condition: Temperature 15~30°C (59~86°F) / Humidity 30~60% Recommended pre and post heater settings are around 30°C(86°F). Lamination is optional. In order to protect the image from physical damage and to decrease image-fading, overlaminates is recommended. Storage: It is recommended to store in the closed original packing in a cool and dry environment Temperature 10°~25°C (50°~77°F), Relative Humidity 50%. Shelf Life: One year stored in original package in recommended condition.

### ASSISTANCE

Call us at 908-686-2200 or visit [DDPMSC.com](http://DDPMSC.com)

### Product Specification Sheet

## SMGPhoto9 Glossy Photo Paper

### PRODUCT OVERVIEW

Extremely glossy surface and advanced coating technology

Designed to offer printers brilliant color reproductions, with high image fidelity

True photo-quality reproductions as well as posters and point of purchase display applications

Allows for high ink load & color saturation with an exceptional dry time

Suitable for indoor and outdoor use

### PRODUCT SUGGESTED APPLICATION

Photo realistic prints

Fine art Reproduction

Posters

Billboards

Kiosks

POP/POS printing

### PRODUCT SPECIFICATIONS

Caliper:	226 microns (9 mil)	Inks:	Eco-Solvent / Solvent / Latex / UV-Cure
Weight:	235g	Width:	36" / 54" / 60"
Base material:	RCP	Length:	30m (100 ft)
Surface:	Glossy	Core:	3"

### PRINTING TIPS

Suitable printing condition: Temperature 15~30°C (59~86°F) / Humidity 30~60% Recommended pre and post heater settings are around 30°C (86°F). Lamination is optional. In order to protect the image from physical damage and to decrease image-fading, overlaminates is recommended. Storage: It is recommended to store in the closed original packing in a cool and dry environment Temperature 10°~25°C (50°~77°F), Relative Humidity 50%. Shelf Life: One year stored in original package in recommended condition.

## SMGRoll-up6 White PET Grey Backed Rollup Glossy Film

### PRODUCT OVERVIEW

6.4 mil white PET film with blackout

Instant dry glossy coating produces photo quality high definition images

Compatible with eco-solvent / true solvent and latex inks

Will not curl, buckle, or warp - offers a robust dimensionally stable final product

### PRODUCT SUGGESTED APPLICATION

Tradeshow panels/graphics

Indoor/outdoor banners

POP/POS displays

Instruction plates

Posters

Retail aisle banners

### PRODUCT SPECIFICATIONS

Caliper: 160 microns (6.4 mil)

Weight: 220g

Base material: Polyester

Surface: Glossy

Inks: Eco-Solvent / Solvent / Latex / UV-Cure

Width: 36" / 50" / 60"

Length: 30m (100 ft)

Core: 3"

### PRINTING TIPS

Suitable printing condition: Temperature 15~30°C (59~86°F) / Humidity 30~60% Recommended pre and post heater settings are around 30°C (86°F). Lamination is optional. In order to protect the image from physical damage and to decrease image-fading, overlaminates is recommended. Storage: It is recommended to store in the closed original packing in a cool and dry environment Temperature 10°~25°C (50°~77°F), Relative Humidity 50%. Shelf Life: One year stored in original package in recommended condition.



**B.C.I.**  
IMAGING

[www.bciimage.com](http://www.bciimage.com)

866 971-1008

**Product Specification Sheet****SMMBacklit8 Premium Solvent Backlit Film Matte****PRODUCT OVERVIEW**

Matte coated translucent PET backlit film

High ink density, vivid colors with glare reducing matte coating

Provides outstanding image resolution with or without light activation

Excellent scratch and water resistancy with an advanced backside light diffusion coating

Compatible in all eco/true solvent, UV, and latex ink printers

**PRODUCT SUGGESTED APPLICATION**

Light box graphic

Backlit tradeshow display

Department store display

Luminous advertising

Bus shelter & Metro illuminated signage

**PRODUCT SPECIFICATIONS**

Caliper: 205 microns (8.2 mil)

Weight: 275g

Base material: Polyester Film

Surface: Matte

Inks: Eco-Solvent/ Solvent / Latex / UV-Cure

Width: 36" / 48" / 54" / 60"

Length: 30m (100 ft)

Core: 3"

**PRINTING TIPS**

Dry time will vary depending on ink type. Lamination is optional. In order to protect the image from physical damage and to decrease image-fading, overlaminates are recommended. Storage: It is recommended to store in the closed original packing in a cool and dry environment Temperature 10°~25°C (50°~77°F), Relative Humidity 50%. Shelf Life: One year stored in original package in recommended condition.

**ASSISTANCE**

Call us at 908-686-2200 or visit [DDPMSC.com](http://DDPMSC.com)

**B.C.I.**  
IMAGING[www.bciimage.com](http://www.bciimage.com)

866 971-1008



### Product Specification Sheet

## SMMCanvas16 Poly/Cotton Semi-Matte Canvas

### PRODUCT OVERVIEW

Light weight poly/cotton blend semi-matte canvas  
Allows for high quality output and color reproduction  
Well suited for wall décor, POP, and more

### PRODUCT SUGGESTED APPLICATION

Wall Decor  
POP/POS

### PRODUCT SPECIFICATIONS

Caliper: 393 microns (15.5 mil)  
Weight: 296 gsm  
Base material: 65% polyester,  
35% cotton base, 1x1 weave  
Surface: Semi-Matte

Ink: Eco-Solvent / Solvent / UV-Cure  
Width: 36" / 50" / 54" / 60" / 72"  
Length: 30m (100 ft)  
Core: 3"

### PRINTING TIPS

Dry time will vary depending on ink type. Dry time will vary depending on ink type. Lamination is optional. In order to protect the image from physical damage and to decrease image-fading, overlaminates are recommended. Storage: It is recommended to store in the closed original packing in a cool and dry environment Temperature 10°~25°C (50°~77°F), Relative Humidity 50%. Shelf Life: One year stored in original package in recommended condition.

### ASSISTANCE

Call us at 908-686-2200 or visit [DDPMSC.com](http://DDPMSC.com)



**B.C.I.**  
IMAGING

[www.bciimage.com](http://www.bciimage.com)

866 971-1008

### Product Specification Sheet

## SMMPhoto8 Solvent Photo Paper Matte

### PRODUCT OVERVIEW

Specialized coating for eco-solvent inks

Long lasting durability for both indoor and outdoor applications

Provides cost effective solution by using a multipurpose base with our advanced IJ receptive coating for photo quality prints.

### PRODUCT SUGGESTED APPLICATION

Indoor and outdoor

Photo realistic prints

Fine art reproduction

Displays: posters, billboards, kiosks

Latex printing media (new printer application)

### PRODUCT SPECIFICATIONS

Caliper: 192 microns (7.8 mil)  
Weight: 230g  
Base material: Paper  
Finish: Matte

Inks: Eco-Solvent / Solvent / Latex / UV-Cure  
Width: 36" / 54" / 60"  
Length: 50m (165 ft)  
Core: 3"

### PRINTING TIPS

Suitable printing condition: Temperature 15~30°C (59~86°F) / Humidity 30~60% Recommended pre and post heater settings are around 30°C(86°F). Lamination is optional. In order to protect the image from physical damage and to decrease image-fading, overlaminates is recommended. Storage: It is recommended to store in the closed original packing in a cool and dry environment Temperature 10°~25°C (50°~77°F), Relative Humidity 50%. Shelf Life: One year stored in original package in recommended condition.

### ASSISTANCE

Call us at 908-686-2200 or visit [DDPMSC.com](http://DDPMSC.com)



**B.C.I.**  
IMAGING

[www.bciimage.com](http://www.bciimage.com)

866 971-1008

### Product Specification Sheet

## SMMPoly8 POPUP8 8mil Smooth Rollup Banner

### PRODUCT OVERVIEW

High opacity blackout film that expresses brilliant color reproduction

It has high image quality along with durability, tear-resistancy and is eco-friendly

High cost effectiveness compared to PET based rollup

Eco-friendly coating (No PVCs)

### PRODUCT SUGGESTED APPLICATION

Tradeshow graphics

Rollup stands

POP/POS displays

Indoor and outdoor signage

### PRODUCT SPECIFICATIONS

Caliper:	195 microns (7.8 mil)	Inks:	Eco-Solvent / Solvent / Latex / UV-Cure
Weight:	160g	Width:	36" / 50"
Base material:	Multi-layer PP	Length:	30m (100 ft)
Surface:	Semi-Matte	Core:	3"

### PRINTING TIPS

Suitable printing condition: Temperature 15~30°C (59~86°F) / Humidity 30~60% Recommended pre- and post heater settings around 30°C(86°F). Lamination is optional. In order to protect the image from physical damage and to decrease image fading, overlaminates is recommended. Storage: It is recommended to store in the closed original packing in a cool and dry environment. Temperature (50°~77°F), Relative Humidity 50%. Shelf Life: One year stored in original package in recommended condition.

### ASSISTANCE

Call us at 908-686-2200 or visit [DDPMSC.com](http://DDPMSC.com)



**B.C.I.**  
IMAGING

[www.bciimage.com](http://www.bciimage.com)

866 971-1008

### Product Specification Sheet

## SMMRoll-up6 White PET Grey Backed Rollup Film Matte

### PRODUCT OVERVIEW

6.4 mil white PET film with blackout produces photo quality high definition images  
Compatible with eco-solvent / true solvent and latex inks  
Will not curl, buckle, or warp  
Offers a robust dimensionally stable final product

### PRODUCT SUGGESTED APPLICATION

Tradeshow panels/graphics  
Indoor/outdoor banners  
POP/POS displays  
Instruction plates  
Posters  
Retail aisle banners

### PRODUCT SPECIFICATIONS

Caliper:	160 microns (6.4 mil)	Inks:	Eco-Solvent / Solvent / Latex / UV-Cure
Weight:	220g	Width:	36" / 50" / 60"
Base material:	White PET	Length:	30m (100 ft)
Surface:	Matte	Core:	3"

### PRINTING TIPS

Suitable printing condition: Temperature 15~30°C (59~86°F) / Humidity 30~60% Recommended pre and post heater settings are around 30°C(86°F). Lamination is optional. In order to protect the image from physical damage and to decrease image fading, overlaminates is recommended. Storage: It is recommended to store in the closed original packing in a cool and dry environment. Temperature 10°~25°C (50°~77°F), Relative Humidity 50%. Shelf Life: One year stored in original package in recommended condition.

**Product Specification Sheet****SMMRoll-up10 10mil Blockout Tradeshow/Rollup PET/PP Film****PRODUCT OVERVIEW**

Scratch-resistant coating prevents the need for lamination  
Perfectly suited for free-standing rollup stands  
Multi-layered polyester film allows for high opacity  
Eco-friendly coating (No PVCs)

**PRODUCT SUGGESTED APPLICATION**

Tradeshow graphics  
Rollup stands  
POP/POS displays  
Indoor and outdoor signage

**PRODUCT SPECIFICATIONS**

Caliper:	260 mic rons (10.2 mil)	Inks:	Eco-Solvent / Solvent / Latex / UV-Cure
Weight:	245g	Width:	36"
Base material:	PET & PP	Length:	30m (100 ft)
Surface:	Satin	Co re:	3"

**PRINTING TIPS**

For best results allow 12-24 hours of drying time (out-gasing) before any application.  
This will maximize the effectiveness of the scratch-resistant coating.  
Storage: It is recommended to store in the closed original packing in a cool and dry environment.  
Temperature: 10°~25°C (50°~77°F), Relative Humidity 50%  
Shelf Life: One year stored in original package in recommended condition.

**ASSISTANCE**

Call us at 908-686-2200 or visit [DDPMSC.com](http://DDPMSC.com)

**B.C.I.**  
IMAGING[www.bciimage.com](http://www.bciimage.com)

866 971-1008

### Product Specification Sheet

## SMMRoll-up14 Gray Backed Tradeshow PET/PP Film

### PRODUCT OVERVIEW

14 multilayer red PET/PP gray backed blackout film  
Matte coating to reduce glare and a high opacity/rigidity  
Superior image quality  
Robust and stable product for all tradeshow/display applications  
Eco-friendly coating (No PVCs)

### PRODUCT SUGGESTED APPLICATION

Indoor/outdoor banners  
Rollup displays  
POP/POS displays  
Tradeshow panels  
Graphics  
Instruction plates  
Retail aisle banners

### PRODUCT SPECIFICATIONS

Caliper:	340 microns (13.6 mil)	Inks:	Eco-Solvent / Solvent / Latex / UV-Cure
Weight:	420g	Width:	36" / 54" / 60"
Base material:	PET & PP	Length:	30m (100 ft)
Surface:	Semi-matte	Core:	3"

### PRINTING TIPS

Dry time will vary depending on ink type. It is necessary to dry up and not to overlap the printed material. Lamination is optional. In order to protect the image from physical damage and to decrease image-fading, overlaminates is recommended. Storage: It is recommended to store in the closed original packing in a cool and dry environment Temperature 10°~25°C (50°~77°F), Relative Humidity 50% Shelf Life: One year stored in original package in recommended condition.

### Product Specification Sheet

## ST600 Easy-Tex Self Adhesive Wallpaper

### PRODUCT OVERVIEW

Sticks to non-porous flat surface

Removable, reusable, repositionable and removes easily with no residue

Sharp, seamless graphics and superior photographic images every time

Ideal for life size photographic cut-outs for walls and wall murals

Indoor and outdoor applications: windows, backlits, doors, sign boards, and other flat surfaces

Applies without wrinkles and does not tear

Eco-friendly coating (approved for California)

### PRODUCT SUGGESTED APPLICATION

Posters

POS/POP printing

Indoor and outdoor banners

Tradeshow panels

Exhibition graphics

Instruction plates

### PRODUCT SPECIFICATIONS

Caliper: 345 microns (13.8 mil)  
Weight: 360g  
Base material: 100% Polyester Woven Fabric  
Surface: Matte

Inks: Eco-Solvent / Solvent / Latex / UV-Cure  
Width: 24" / 36" / 54" / 60"  
Length: 30m (100 ft)  
Core: 3"

### PRINTING TIPS

Suitable printing condition: Temperature 15~30°C (59~86°F) / Humidity 30~60% Recommended pre and post heater settings are around 30°C (86°F). Lamination is optional. In order to protect the image from physical damage and to decrease image-fading, overlaminates is recommended. Storage: It is recommended to store in the closed original packing in a cool and dry environment Temperature 10°~25°C (50°~77°F), Relative Humidity 50%. Shelf Life: One year stored in original package in recommended condition.

### Product Specification Sheet

## SMSPOSTER7 Satin Poster Paper

### PRODUCT OVERVIEW

Provides cost effective solutions for short-term photo quality needs  
Eco-friendly coating for solvent and latex inks  
Made with a paper base and treated for high opacity  
Durable enough for both indoor and outdoor use

### PRODUCT SUGGESTED APPLICATION

Posters  
Graphics  
Photo realistic prints  
Retail displays  
Indoor and outdoor posters and signage

### PRODUCT SPECIFICATIONS

Caliper:	172 microns (6.9 mil)	Inks:	Solvent / Latex / UV-Cure
Weight:	150g	Width:	54" / 60"
Base material:	Paper	Length:	46m (150 ft)
		Core:	3"

### PRINTING TIPS

Suitable printing condition: Temperature 15~30°C (59~86°F) / Humidity 30~60% Recommended pre and post heater settings are around 30°C(86°F). Lamination is optional. In order to protect the image from physical damage and to decrease image fading, overlaminates is recommended. Storage: It is recommended to store in the closed original packing in a cool and dry environment. Temperature (50°~77°F), Relative Humidity 50%. Shelf Life: One year stored in original package in recommended condition.

### ASSISTANCE

Call us at 908-686-2200 or visit [DDPMSC.com](http://DDPMSC.com)



**B.C.I.**  
IMAGING

[www.bciimage.com](http://www.bciimage.com)

866 971-1008



**Product Specification Sheet****SMSRoll-up10 10mil Blockout Tradeshow/Rollup PET/PP Film****PRODUCT OVERVIEW**

Scratch-resistant coating prevents the need for lamination  
Perfectly suited for free-standing rollup stands  
Multi-layered polyester film allows for high opacity  
Eco-friendly coating (No PVCs)

**PRODUCT SUGGESTED APPLICATION**

Tradeshow graphics  
Rollup stands  
POP/POS displays  
Indoor and outdoor signage

**PRODUCT SPECIFICATIONS**

Caliper:	260 mic rons (10.2 mil)	Inks:	Eco-Solvent / Solvent / Latex / UV-Cure
Weight:	245g	Width:	36"
Base material:	PET & PP	Length:	30m (100 ft)
Surface:	Satin	Co re:	3"

**PRINTING TIPS**

For best results allow 12-24 hours of drying time (out-gasing) before any application.  
This will maximize the effectiveness of the scratch-resistant coating.  
Storage: It is recommended to store in the closed original packing in a cool and dry environment.  
Temperature: 10°~25°C (50°~77°F), Relative Humidity 50%  
Shelf Life: One year sto red in original package in recommended condition.

**ASSISTANCE**

Call us at 908-686-2200 or visit [DDPMSC.com](http://DDPMSC.com)

**B.C.I.**  
IMAGING[www.bciimage.com](http://www.bciimage.com)

866 971-1008

# Diamond Digital Inkjet Media

## **AQUEOUS MEDIA**

### **Photo Paper**

10mil M/P Premium Gloss Photo Paper  
10mil M/P Premium Satin Photo Paper  
8mil M/P Premium Gloss Photo Paper  
8mil M/P Premium Satin Photo Paper  
8mil M/P Premium Gloss PSA Photo Paper  
8mil M/P Premium Satin PSA Photo Paper

### **Display / Films**

10mil Blockout/Tradeshow PET Roll-up Matte  
14mil Grey Backed Tradeshow PET Film Matte  
6.4mil White Gloss PET Grey Backed Roll-up Film  
5.4mil White Matte PET Grey Backed Roll-up Film  
8.6mil Matte Water Resistant PET Backlit Film  
8.6mil M/P Gloss PET Backlit Film

### **Banner / Signage**

6.1mil Matte Polypropylene Banner  
8.2mil Matte Polypropylene Banner  
10oz Matte Super Smooth Scrim Banner  
7.4mil Matte Adhesive-back  
9mil Gloss M/P Adhesive-back  
9mil Matte Adhesive-back  
13.8mil Easy-Tex Removable-

## **SOLVENT / UV / LATEX MEDIA**

### **Photo Paper**

7.8mil Gloss Photo Paper  
7.8mil Matte Photo Paper  
9mil Gloss Photo Paper  
13mil Gloss PSA Blueback Photo Paper  
9mil Matte Wet Strength Poster Paper

### **Display / Films / Banner**

8.2mil Gloss Backlit Film  
8.2mil Matte Backlit Film  
10mil Blockout/Tradeshow PET Roll-up Matte  
14mil Grey Backed Tradeshow PET Film Matte  
6.5mil White Gloss PET Grey Backed Roll-up Film



**B.C.I.**  
IMAGING

[www.bciimage.com](http://www.bciimage.com)

866 971-1008