



2402 Series - Avery Dennison® HV1200 High Visibility Series Reflective Film

FDC 2402 Series is Avery Dennison® HV1200 High Visibility Reflective Film. This product is a premium quality, enclosed lens, retro-reflective film which meets or exceeds ASTM D4956 for reflectivity. Designed for screen printing as well as computer cutting equipment, it provides excellent cutting, weeding, transferring and conforming characteristics. To order punched material, use part number 2452.

- Film Technology:** **Retroreflective**
- Film Thickness:** **4.5 mil.**
- Media Color:** **12 Colors-** see color chart
- Blockout:** **Yes**
- Finish:** **Gloss**
- Outdoor Durability:** **7 Years**
- Adhesive/Color:** **Permanent/Clear/Pressure Sensitive**
- Liner:** **90# Stayflat**
- Conformability:** **Flat and Simple Curves, Rivets and Corrugations**
- Printing:** **Thermal Transfer, Screen**
 (*A print test is recommended prior to production to determine the suitability of this product given a particular printer, rip, ink type and ink set. Allow at least 24 hours for inks to dry and properly outgas prior to lamination.)
- Temperature:** **Minimum Application Temperature is 50°F**
Service Temperature Range is -40°F to 180°F
 (*Temperature applies for: graphics, substrate and environment.)
- Shelf Life:** **1 Year -** when stored at temperatures under 73°F and 50% R.H.

Note: For further information regarding: printing, substrate cleaning, application, maintenance, durability and removal please review the corresponding instructional bulletin available at www.fdcfilms.com.

Warranty: Data provided by FDC is for general information only. This data is not to be used for exacting specification purposes. Always pretest product. Suitability for any given application is the responsibility of the user. Since FDC cannot control the conditions under which the products referred to herein may be used or handled, it can make no guarantee as to the effectiveness, safety or applicability with respect hereto. FDC's only obligation shall be to replace such quantity of product proven to be defective. FDC shall not be liable for any injury, loss or damage, direct or consequential, arising out of the use or the inability to use the product. Before using, the user shall determine the suitability of the product for his intended use, and user assumes all risk and liability whatsoever in connection therewith. The seller, FDC, shall not be liable for any default or delay caused by contingency beyond its control or the control of its supplier including but not limited, short or reduced supply of fuel, or other integral components of the product.

EW