



## WINDOW GRAPHICS

### SPMPWE

For Exterior Use

#### Perforated One-Way Vision Film

With a Removable Acrylic Adhesive and a Clear Film Release Liner

Catalina Graphic Films' Perforated One-Way Vision Film for exterior use is a flexible matte white/black calendered film coated with a clear removable pressure sensitive adhesive and a clear film backing

RECOMMENDED APPLICATIONS
• Window
• Indoor
• Outdoor

OVERVIEW
<b>Face Film</b> 8.0 mil Matte White on the Print Side/Black on the Adhesive Side, Flexible Vinyl. Perforation Size is 1.5mm
<b>Adhesive</b> .001 Clear Acrylic Pressure Activated Removable
<b>Liner</b> .007 mils Clear Film Backing
<b>Open Area</b> 50/50
<b>Gloss Level</b> Matte
<b>Outdoor Durability</b> Up to 3 Years. 6 months for clean removal. Adhesion may increase with time.

SPECIFICATIONS
<b>Application</b> Ideal for fleet graphics, exterior-mount windows, glass doors or other transparent surfaces for short-term P.O.P., retail window graphics or similar applications requiring graphics on one side and a clear, unobstructed view through the other. Not recommended for long-term or large scale applications (e.g. building wraps).
<b>Print Methods</b> Compatible with screen printing, solvent, eco-solvent, thermal transfer and UV-cure inks. NOT FOR USE WITH LATEX INKS. Print image on vinyl side, not on release liner.
<b>Minimum Application Temperature</b> +40° F
<b>Service Temperature Range</b> 0° F To +140° F.
<b>Adhesion</b> 10 ± 2 oz/in (180° adhesion from SS, 20 minute room temperature dwell)
<b>Water Resistance</b> Fair. Immersion in water not recommended. If exposed to rain, an optically clear, compatible overlaminant can be used to prevent holes from filling with water.
<b>Solvent Resistance</b> Fair
<b>Shelf Life</b> 6-months when stored under conditions of 70°F and 50% relative humidity
<b>Hole Patterns Available</b> Standard View (1.5mm holes)
<b>Window Application</b> Apply to dry, clean glass surface. Use mild soap and water, rinse and dry the glass well. Do not use ammonia or other solvent based glass cleaners (e.g., Windex) prior to application.

The above information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. They are given without guarantee and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)

To order or request product samples,  
contact your local authorized dealer or call direct

Customer Service **800-333-3136** or visit our websites:

 **CATALINA**  
GRAPHIC FILMS  
INCORPORATED

27001 Agoura Road  
Suite 100  
Calabasas Hills  
California 91301

Phone: (818) 880-8060  
Fax: (818) 880-1144  
Atlanta Sales: (800) 922-5880  
Chicago Sales: (800) 766-4939  
E-mail: [info@catalinagraphicfilms.com](mailto:info@catalinagraphicfilms.com)



[CatalinaGraphicFilms.com](http://CatalinaGraphicFilms.com)



[MojaveDigitalMedia.com](http://MojaveDigitalMedia.com)