

WINDOW GRAPHICS VINYL FOR HP INDIGO



SPMSAIN

4.0 mil. Sign-Ad® Matte White Calendered Vinyl With a Low-Tack Removable Acrylic Adhesive and a 90# StayFlat Release Liner

HP Certified by RIT

Catalina Graphic Films' Mojave Digital Media family of HP INDIGO® certified print substrates is specially coated for printing with the HP Indigo line of digital printers.

| RECOMMENDED APPLICATIONS | | |
|--------------------------|--------|--|
| • D | ecals | |
| • W | /indow | |
| • In | door | |
| • Oı | utdoor | |

| OVERVIEW | |
|-------------------|--|
| Face Film | 4.0 mil. Sign-Ad® Matte White Calendered Vinyl |
| Adhesive | Low-Tack Removable Acrylic |
| Liner | 90# Stayflat |
| Opacity | Good |
| Gloss Level | Matte |
| Indoor Durability | Up to 2 Years |

| SPECIFICATIONS | | | |
|---|---|--|--|
| Application | Sign-Ad IN is a matte white, flexible vinyl with a specially formulated low-tack adhesive used for interior and exterior applications with no solvents required. This product is intended for use as high quality, interior exterior marking or decal in applications requiring easy removeability with no adhesive residue. Use as alternative to flood coating clear film with white ink. No solvents are needed for the application or removal of Sign-Ad. | | |
| Print Methods | For printing with HP Indigo line of digital printers | | |
| Minimum Surface/Ambient Air Application Temperature | +45° F | | |
| Service Temperature Range | -10°F to 120°F | | |
| Typical Film Caliper (w/Adhesive) | 4.3 - 4.5 Mils. With Adhesive | | |
| Adhesion | 10 – 12 Oz. / in. | | |
| Water Resistance | Excellent. | | |
| Chemical Resistance | Good for most petroleum solvents and lower aliphatic alcohols. For ultimate solvent resistance, edge sealing is recommended. | | |
| Shelf Life | Two (2) year when stored under conditions of 70°F and 50% relative humidity. | | |
| Printability | Leave 1/4" bleed. | | |

The above information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. They are given without guarantee and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)

> To order or request product samples, contact your local authorized dealer or call direct

Customer Service 800 - 333 - 3136 or visit our websites:



27001 Agoura Road Phone: (818) 880-8060 Suite 100 Calabasas Hills California 91301

Fax: (818) 880-1144

Atlanta Sales: (800) 922-5880 Chicago Sales: (800) 766-4939

E-mail: info@catalinagraphicfilms.com



