



MAGNETICS

SPMMAG

12.0, 20.0 & 30.0 mil. Flexible Magnetic Vinyl

Lead-Free Bonded Iron Ferrite with Multi-Pole Magnetization

Catalina Graphic Films' Mojave Magnetics are lead-free bonded iron ferrite with multi-pole magnetization resulting in superior holding power on most metallic surfaces.

RECOMMENDED APPLICATIONS
• Decals
• Fleet without Rivets
• Indoor
• Outdoor

OVERVIEW	
Face Film	Matte White Vinyl Film
Adhesive	None
Liner	None
Opacity	Excellent
Gloss Level	Gloss
Outdoor Durability	Up to 1 Year
Indoor Durability	Up to 3 Year

SPECIFICATIONS	
Application	Ideal uses include car signs, business cards, promotional products, message boards and other promotional point-of-purchase displays and advertising specialties.
Print Methods	Silk screen, foil hot stamping, label, offset and digital printing processes
Total Product Thickness	12 mil = .30 mm 20 mil = .51 mm 30 mil = .76 mm
Minimum Application Temperature	60° F.
Service Temperature Range	60° F +
Magnetization	Multi-pole magnetization. Magnetic strength at or above .020 Mil thickness is ample for car signs.
Minimum Magnetic Pull lbs. per sq. ft. (kg per m2)**	12 mil = 30 (146) 20 mil = 60 (293) 30 mil = 85 (415)
Water Resistance	Yes
Shelf Life	2 Years

The above information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. They are given without guarantee and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)

To order or request product samples,
contact your local authorized dealer or call direct

Customer Service **800-333-3136** or visit our websites:



27001 Agoura Road
Suite 100
Calabasas Hills
California 91301

Phone: (818) 880-8060
Fax: (818) 880-1144

Atlanta Sales: (800) 922-5880
Chicago Sales: (800) 766-4939

E-mail: info@catalinagraphicfilms.com

