

Solvent **ES690--**
For Solvent, Latex, UV ink

Certified for
HP Latex Inks

GREEN BACKLIT

The biggest feature of coating layer is brighter white and does not use PVC components at all. A bright white tone can produce the splashes of color. Because the coating layer does not use PVC, it provides curling-free as well. ES690 is made of 7 mil polyester film with satin finish. The satin surface ensures high color density, quality image, and anti-glare. ES690 is the perfect product for small and large jobs for backlit applications

APPLICATION

Light box graphic
Backlit Trade show display
Department store display
luminous advertising
Bus shelter & Metro illuminated signage


SPECIFICATION

Caliper	205 micron (8.2 mil)
weight	275g
Base material	Polyester film
Surface	Semi Matte
Width	36", 42", 50", 60"
Length	30m (100 ft)
Core	3"

COMPATIBILITY

(★ Excellent, ◎ Very good, ○ Good, △ Fair, X Not good)

Ink Compatibility



Printer Compatibility

Most Solvent, Eco Solvent Printing system and LATEX.
HP, Epson, Roland, Mimaki, Mutoh, Seiko, Oce

TECHNICAL DATA

Caliper	205micron	ASTM D645
Gloss	5/8	ASTM D2457
L.a.b	85/ 1 / -7	ANSI T D50/2 ² /Abs/No

GUIDELINES

- Printing Tip** Dry time will vary depending on ink type.
It is necessary to dry up and not to overlap the printed material.
- Lamination:** Lamination is optional. In order to protect the image from physical damage, overlaminates is recommended.
- Storage:** It is recommended to store in the closed original packing in a cool and dry environment
Temperature 10°~30°C (50°~86°F), Humidity 35~65% RH
- Shelf Life:** One year stored in original package in recommended condition

Information provided here is subject to our test criteria and subject to change without prior notice. No media warranty is implied. All material should be tested by purchaser to determine final suitability. Printer and ink change may affect results.