

OVERLAMINATES

POLYESTER OVERLAMINATES

LM1CL

1.0 mil. Clear Polyester

With a Permanent Acrylic Adhesive and a Clear Film Liner

Catalina Graphic Films' Mojave Digital Media family of Overlaminates enhance overall graphic depth and gloss while protecting printed materials from UV radiation, environmental elements and general abuse.

RECOMMENDED APPLICATIONS		
•	Simple Curves	
•	Decals	
•	Indoor	

OVERVIEW	
Face Film	1.0 ± 0.1 mils clear, polyester
Adhesive	1.0 ± 0.1 mils P-22, clear, acrylic, pressure- activated, high-performance permanent
Liner	2-mil clear, silicone-coated-one-side, clear film
Opacity	Clear
Gloss Level	Gloss
Outdoor Durability	Indoor Only

SPECIFICATIONS			
Application	This product is intended for use as an overlaminating film as a protective layer for printed substrates that are applied to indoor surfaces.		
Product Thickness (Film Only)	1.0 - 1.1 mils		
Minimum Surface/Ambient Air Application Temperature	+35° F.		
Service Temperature Range	-20° F to +150° F.		
Water Resistance	Good.		
Solvent Resistance	Good for most petroleum solvents and lower aliphatic alcohols. For ultimate solvent resistance, edge sealing is recommended.		
Adhesion	40+ oz. per lineal inch width (180 peel from Stainless Steel; 15-minute, room temperature dwell on test panel).		
Shelf Life	One (1) year when stored under conditions of 70°F and 50% relative humidity.		

The above information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. They are given without guarantee and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)



27001 Agoura Road Phone: (818) 880-8060 Suite 100 Calabasas Hills California 91301

Fax: (818) 880-1144

Atlanta Sales: (800) 922-5880 Chicago Sales: (800) 766-4939

E-mail: info@catalinagraphicfilms.com

To order or request product samples, contact your local authorized dealer or call direct

Customer Service 800 - 333 - 3136 or visit our websites:



