

OVERLAMINATES

CALENDERED OVERLAMINATES

LM3LL

3.0 mil. Luster Flexible Vinyl • with UV Protection With a Permanent Acrylic Adhesive and a 53# Paper Liner

Catalina Graphic Films' Mojave Digital Media family of Overlaminates enhance overall graphic depth and gloss while protecting printed materials from UV radiation, environmental elements and general abuse.

| RECOMMENDED APPLICATIONS | | |
|--------------------------|----------------------|--|
| • | Simple Curves | |
| • | Decals | |
| • | Fleet without Rivets | |
| • | Indoor | |
| • | Outdoor | |

| OVERVIEW | |
|--------------------|---|
| Face Film | 3.0 ± 0.2 mils semi-gloss, clear, flexible vinyl |
| Adhesive | 1.0 ± 0.1 mils P-22, clear, acrylic, pressure- activated, high-performance permanent |
| Liner | 53-lb. (3.1 \pm 0.2 mils) white, polyethylene-coated-one-side, silicone-coated-one-side paper |
| Opacity | Clear |
| Gloss Level | Luster |
| Outdoor Durability | Up to 5 Years Unprinted |

| SPECIFICATIONS | | | |
|--|---|--|--|
| Application | This product is intended for use as an overlaminating film with slight glare-reducing protective layer with luster properties on printed substrates that are applied to indoor and outdoor surfaces such as bus or automobile markings, buildings; signage; etc. Flat and simple curves only. | | |
| Product Thickness (Film Only) | 3.0 - 3.2 mils | | |
| Minimum Surface/Ambient Air Application Temperature | +35° F. | | |
| Service Temperature Range | -20° F to +150° F. | | |
| Water Resistance | Good. | | |
| Solvent Resistance | Good for most petroleum solvents and lower aliphatic alcohols. For ultimate solvent resistance, edge sealing is recommended. | | |
| Adhesion | 40+ oz. per lineal inch width (180 peel from Stainless Steel; 15-minute, room temperature dwell on test panel). | | |
| UV Resistance | Up to 5 Years Unprinted | | |
| Shelf Life | One (1) year when stored under conditions of 70°F and 50% relative humidity. | | |

The above information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. They are given without guarantee and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)

To order or request product samples, contact your local authorized dealer or call direct

Customer Service 800 - 333 - 3136 or visit our websites:



27001 Agoura Road Phone: (818) 880-8060 Suite 100 Calabasas Hills California 91301

Fax: (818) 880-1144

Atlanta Sales: (800) 922-5880 Chicago Sales: (800) 766-4939

E-mail: info@catalinagraphicfilms.com



