

20oz. Wallcover Sand (Woven, Fabric Back)



866 971-1008 www.bciimage.com



20oz. Wallcover Sand is an environmentally friendly Type II PVC wallcovering that meets EPA requirements for low VOC-emitting products and Class A Fire Rating. Free of Phthalate, this wallcovering is ideal for sensitive environments, such as healthcare facilities, schools and more. 20oz. Wallcover Sand is an ideal product for print service providers, design firms and sign companies looking to break into the decor market. Compatible with latex, eco-solvent, solvent and UV inks.

Benefits	Applications	Customers
<ul style="list-style-type: none">• Type II PVC• Commercial Grade, Class A Fire Rating• Meets EPA requirements for low VOC emitting products• Phthalate free substrate• Compatible with all latex, eco-solvent, solvent and UV Inks	<ul style="list-style-type: none">• Corporate environment murals• Healthcare facilities• Retail• Entertainment venues	<ul style="list-style-type: none">• Large format print service• Design firm/ad agency• In-house• Federal government• Schools• Sign companies

SPECIFICATIONS

Material Type	100% PVC Face
Backing	Polyester/Cotton Woven Backing
Gauge	18 mil
GSM	448
Weight	20 oz./linear yard
Whiteness	89.44
Brightness	87.10
Opacity	100%
Gloss Level	6.4 (60)
Finish	Liquid coating can be applied for extra protections and finish.
RIP & Printer Media Settings	Optimal printer settings will vary from printer manufacturers. A suggested starting point is setting the pre and post heaters to 122° F (50° C). For the best and most consistent results a profile should be created using an external color calibrator in conjunction with your RIP and color matching software. If a custom profile is not available, the on-board media setting, Cast Vinyls, typically used for vehicle wraps, is a good place to start.
Light Fastness	The fading time of inkjet ink is a direct result of the inks that you choose to use and the environment where the print is displayed. Contact the ink manufacturer for light-fastness data.
L*	94.33
A*	-0.18
B*	-0.62
Flame Rating	Class A
Core Size	3" ID core
Optimal Service Environment	For printing: 60°-80° F, 50% Relative Humidity. For end use: -40°-176° F (-40°-80° C).
Ideal Storage Conditions	70° F (21° C), 50% R.H. (a controlled environment is recommended); store vertically in original packaging.
Color	Bright white PVC
Ink Compatibility	Compatible with all low-solvent, solvent, UV-curable and latex printers.
Shelf Life	1 year storage in original package under recommended storage conditions above.

SKU

Size

WCOS205475	54 in x 75' ft (Sample Roll)
WCOS2054150	54 in x 150 ft

Product Performance & Suitability: All of the descriptive information and recommendations should be used only as a guide. Furnishing such information and recommendations shall in no event constitute a warranty of any kind. All purchasers shall independently determine the suitability of the material for the purpose for which it is purchased. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither the seller nor manufacturer shall be liable either in tort or in contract for any loss or damage, direct, incidental or consequential (including loss of profits or revenue) arising out of the use of or the inability to use the product. No statement or recommendation not contained herein shall have any force or effect unless in agreement signed by officers of seller and manufacturer.