

225gsm Gloss Solvent PE Paper



866 971-1008 www.bciimage.com



This versatile resin coated gloss photo paper has been created specifically for solvent, eco-solvent, and latex printers. Your prints will instantly be dry when coming off the printer creating an efficient work environment for high production runs. It also allows you to thermally laminate this material without having to wait. With a wide color gamut and a gloss finish, this photo paper looks exceptional when it comes to detail and quality. Whether it's photo reproductions, point of purchase displays or posters, this is a perfect go-to product to give you the results you are looking for every time.

Benefits	Applications	Target Customers
<ul style="list-style-type: none">• Gloss finish with wide color gamut• Can be thermally laminated• Resin coated – instant-dry	<ul style="list-style-type: none">• Point of purchase• Posters• Fine Art reproduction	<ul style="list-style-type: none">• Retail• Fine Art reproduction houses• Large format print services

SPECIFICATIONS

Material Type	PE paper
Gauge	9.5 mil
Applications	Posters, Indoor displays, photo reproductions
Product Benefits	Heavyweight, which makes handling easy, instant-dry, scratch-resistant
Weight	225 gsm
Finish	No post processing or finishing is required.
Whiteness	'>145%
Opacity	'>90%
Gloss Level	90 ± 5%
RIP & Printer Media Settings	For the best and most consistent results, a profile should be created using a calibrator in conjunction with your RIP and color matching software. If custom profiles are not available, try a few different on-board media settings to achieve optimum performance.
Light Fastness	The fading time of inkjet ink is a direct result of the inks that you choose to use and the environment where the print is displayed. Contact the ink manufacturer for light-fastness data.
Core Size	2" ID core
Water Resistance	Instant-dry and water-resistant.
Optimal Service Environment	Optimal Print Environment: 70° F (21° C), 50% R.H Optimal Service Environment for Printing: 60 -80° F, 50% Relative Humidity. Handling Recommendations: Due to the absorptive nature of the coating, you should avoid touching the coated surface. It's always recommended that cotton gloves be used when handling inkjet coated materials. Rolls are supplied with the coated side facing out.
Ideal Storage Conditions	70° F (21° C), 50% R.H. (a controlled environment is recommended); store in original packaging.
Color	L 93.9 ± 1.0 a -0.3 ± 0.5 b -1.6 ± 0.7 delta b 12.4 ± 0.8
Ink Compatibility	Compatible with all inkjet printers using eco-solvent, solvent, latex and UV-curable inks.
Shelf Life	1 year from the ship date when stored in proper conditions.

SKU
Size

Product Performance & Suitability: All of the descriptive information and recommendations should be used only as a guide. Furnishing such information and recommendations shall in no event constitute a warranty of any kind. All purchasers shall independently determine the suitability of the material for the purpose for which it is purchased. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither the seller nor manufacturer shall be liable either in tort or in contract for any loss or damage, direct, incidental or consequential (including loss of profits or revenue) arising out of the use of or the inability to use the product. No statement or recommendation not contained herein shall have any force or effect unless in agreement signed by officers of seller and manufacturer.