

Classic Gloss 155^{155SGL}

Gloss Lightblock Roll-Up Polyester Film

Applications

- Roller banner displays

Benefits

- Premium roller banner material – grey back, 98% opacity
- High gloss bright-white front surface
- Optimum ink adhesion
- Scratch and water resistant
- Antistatic treatment avoids attracting dust and slipping in the printer
- Stiff, perfect flatness

Post Printing Information for Latex & Solvent Inks:

As with all filmic media, this product must be allowed to “gas-out” after printing.

This can be achieved by leaving the prints face up, ideally 24 hours, to set and harden the unique scratch resistant properties.

If unable to do this e.g. with a long print run, after printing the roll stand it vertically and loosely unwind as much as possible, to allow air in and gases out.

Printability:



Thickness:

155 μ	6.1 mil	225 gsm
-----------------	-------------------	-------------------

Available widths:

914 36"	1067 42"	1270 50"
-------------------	--------------------	--------------------

Recommended Conditions:

Printroom	15°C - 30°C	30% - 65% RH
Usage	-40°C - 80°C	10% - 90% RH
Storage	10°C - 20°C	20% - 50% RH



* from 3rd Gen HP or later

The information provided herein is correct to the best of our knowledge. No liability for any errors, facts or opinions is accepted. We recommend users make their own assessments to satisfy themselves as to the suitability of this product for their application. Copyright Sensitizers Group 2016