

Classic Matte 290 290SML

Matte Lightblock Pop-Up Polyester Film

Applications

- Pop-up displays

Benefits

- Premium roll-up material - grey back, 98% opacity
- Anti-reflective, matte, bright-white front surface
- Optimum ink adhesion, fast drying
- Scratch and water resistant
- Antistatic treatment avoids attracting dust
- No slipping in the printer, ideal for perfect pop-ups
- Stiff, perfect flatness

Post Printing Information for Latex & Solvent Inks:

As with all filmic media, this product must be allowed to “gas-out” after printing.

This can be achieved by leaving the prints face up, ideally 24 hours, to set and harden the unique scratch resistant properties.

If unable to do this e.g. with a long print run, after printing the roll stand it vertically and loosely unwind as much as possible, to allow air in and gases out.

Recommended Conditions:

Printroom	59°F - 85°F 15°C - 30°C	30% - 65% RH
Usage	50°F - 17°F 10°C - 80°C	10% - 90% RH
Storage	50°F - 68°F 10°C - 20°C	20% - 50% RH

Printability:



Thickness:

290 μ	11.4 mil	398 gsm
-----------------	--------------------	-------------------

Available widths:

914 36"	1270 50"	1524 60"
-------------------	--------------------	--------------------

