

Printability:











Thickness:

~500 ~20 350 mil ±20 gsm

Available widths:

1300 51.2"

Interiors 500

Non-woven printable wallcoverings

Applications Customised wallcoverings for tough environments including POS, retail stores, hotels, schools, offices and hospitals

Certified for **HP Latex Inks**

KERNOWJET

INTERIORS

Benefits

- Easy handling and fast application paste the wall not the wallcovering
- Removable dry without residues or damage to the walls
- Perfect dimensional stability zero shrinkage for perfect seams
- Washable using mild soap and a sponge or cloth
- Breathable and Bio-Pruf®: inhibits the growth of micro-organisms such as bacteria and mould
- Non-woven substrate with top-coated vinyl
- Fire rated: Euro class B s1d0, M1 and B1
- Certified to work with ClearShield Wall Armor for additional stain, scratch and abrasion resistance
- Check the swatch book and literature for the 13 different embossing patterns

Please read the installation instruction before applying.

Post Printing Information for Solvent Inks:

As with all filmic media, this product must be allowed to "gas-out" after solvent printing. This can be achieved by leaving the prints face up, ideally 24 hours. If unable to do this e.g. with a long print run, after printing the roll stand it vertically and loosely unwind as much as possible, to allow air in and solvent out.

Recommended Conditions:

Printroom	15°C - 30°C	30% - 65% RH
Usage	-40°C - 80°C	10% - 90% RH
Storage	10°C - 20°C	20% - 50% RH

