

Opaline Matte 215^{215SMB}

Matte Backlight Polyester Film

Applications

- Lightboxes
- Backlit applications indoor and outdoor

Benefits

- Front print on matte high-resolution coating
- Bright light-diffusing back-coat hides light elements
- With solvent inks: reverse or front print - can be illuminated from either side
- Optimum day/night performance
- Superb gamut when back-lit
- Weather resistant for outdoor displays
- Antistatic treatment avoids attracting dust and slipping in the printer

Post Printing Information for Latex & Solvent Inks:

As with all filmic media, this product must be allowed to "gas-out" after printing. This can be achieved by leaving the prints face up, ideally 24 hours, to set and harden the unique scratch resistant properties. If unable to do this e.g. with a long print run, after printing the roll stand it vertically and loosely unwind as much as possible, to allow air in and gases out.

Recommended Conditions:

Printroom	59°F - 86°F 15°C - 30°C	30% - 65% RH
Usage	40°F - 176°F -40°C - 80°C	10% - 90% RH
Storage	50°F - 68°F 10°C - 20°C	20% - 50% RH

Printability:



Thickness:

215 μ	8.5 mil	285 gsm
-----------------	-------------------	-------------------

Available widths:

1270 50"	1372 54"	1524 60"
--------------------	--------------------	--------------------

