

Heat-Activated Laminating Films

Jet Guard[®], ThermaShield[®]

Laminating Films

Jet Guard[®]

A premium family of low temperature heat-activated over-laminating films available in standard finishes with UV protection or unique textured finishes for specialty applications.

Jet Guard contains the optimal 'film to adhesive ratio' for exceptional adhesive flow to eliminate 'silvering' while the polyester content ensures maximum image protection and rigidity.

Jet Guard[®] UV is designed to provide UV protection, high-impact color enhancement, sharp contrast and the durability needed to withstand the demands of your displays environment. Available in gloss, luster and matte finishes.

Jet Guard[®] Deep Crystal[®] is a unique over-laminating film featuring a durable, scratch-resistant, crystal-textured satin finish. Because of its texture, "Deep Crystal" hides finger prints and scratches, making it a great choice for displays that need a lot of handling. Deep Crystal has become one of the most popular SEAL over-laminates worldwide.

Jet Guard[®]

Crystal[®] Matte offers a brilliant clear matte finish that reduces glare for easy viewing while optimizing image colors and contrast. Because of its unique multi-layer construction, "Crystal Matte" will not mute bright colors like typical matte films.



Application Tip

SEAL over-laminate films consist of many different types of film, such as polyester (low cost- rigid), vinyl (medium cost-flexible) and polycarbonate (higher cost and very durable). They are also offered in an endless array of finishes and different textures.

Selection should be based on visual esthetics and lighting conditions to ensure a balance of "optimal viewing" of the displayed image. Additionally, because each film has different performance characteristics it is essential to understand the application requirements or demands when selecting a film type.

ThermaShield[®]

This cost-effective range is designed to protect, enhance, and add rigidity to images for a variety of applications.

ThermaShield[®] – Gloss, Luster and Matte – provides the best in terms of value and performance. Select Gloss for dramatic enhancement, Luster for a softer effect and Matte to reduce glare and reflection on your image. Thermashield is available in a wide array of roll widths and film thickness from 1.7, 3, 5 or 10 mils.



For more information on SEAL over-laminating films, please refer to the SEAL Material Guide or contact your authorized SEAL representative.

Over-laminate

Print

Heat-Activated

Heat-Activated Laminating Films

Jet Guard®, **ThermaShield®**



www.bciimage.com
866 971-1008

Product Range

| Product | Catalog Number | Size | Product | Catalog Number | Size |
|---------------------------|----------------|--------------------------|----------------------------|----------------|---------------------------|
| Jet Guard® UV Gloss 3mil | 62102 | 25" x 250' (635mm x 76m) | Jet Guard® Deep Crystal | 624110 | 38" x 150' (965mm x 46m) |
| Jet Guard® UV Gloss 3mil | 62103 | 38" x 250' (965mm x 76m) | Jet Guard® Deep Crystal | 624111 | 51" x 150' (1.29mm x 46m) |
| Jet Guard® UV Gloss 3mil | 62104 | 43" x 250' (1.09 x 76m) | Jet Guard® Deep Crystal | 624112 | 55" x 150' (1.40mm x 46m) |
| Jet Guard® UV Gloss 3mil | 62105 | 51" x 250' (1.29 x 76m) | Jet Guard® Deep Crystal | 624113 | 61" x 164' (1.55mm x 50m) |
| Jet Guard® UV Gloss 3mil | 62106 | 55" x 250' (1.40 x 76m) | Jet Guard® Crystal Matte | 624115 | 38" x 150' (965mm x 46m) |
| Jet Guard® UV Gloss 3mil | 62107 | 61" x 250' (1.55 x 76m) | Jet Guard® Crystal Matte | 624116 | 51" x 150' (1.29mm x 46m) |
| Jet Guard® UV Gloss 3mil | 62101 | 38" x 25' (965mm x 7.6m) | Jet Guard® Crystal Matte | 624117 | 55" x 150' (1.40mm x 46m) |
| Jet Guard® UV Gloss 3mil | 62112 | 25" x 250' (635mm x 76m) | Jet Guard® Crystal Matte | 624118 | 61" x 164' (1.55mm x 50m) |
| Jet Guard® UV Gloss 5mil | 62113 | 38" x 250' (965mm x 76m) | ThermaShield® Gloss 1.7mil | 62402 | 38" x 500' (965mm x 152m) |
| Jet Guard® UV Gloss 5mil | 62114 | 43" x 250' (1.09 x 76m) | ThermaShield® Gloss 1.7mil | 62403 | 51" x 500' (1.29 x 152m) |
| Jet Guard® UV Gloss 5mil | 62115 | 51" x 250' (1.29 x 76m) | ThermaShield® Gloss 1.7mil | 62404 | 38" x 25' (965mm x 7.6m) |
| Jet Guard® UV Gloss 5mil | 62116 | 55" x 250' (1.40 x 76m) | ThermaShield® Gloss 3mil | 62406 | 38" x 500' (965mm x 152m) |
| Jet Guard® UV Gloss 5mil | 62117 | 61" x 250' (1.55 x 76m) | ThermaShield® Gloss 3mil | 62410 | 43" x 500' (1.09 x 152m) |
| Jet Guard® UV Gloss 5mil | 62111 | 38" x 25' (965mm x 7.6m) | ThermaShield® Gloss 3mil | 62407 | 51" x 500' (1.29 x 152m) |
| Jet Guard® UV Gloss 10mil | 62122 | 25" x 250' (635mm x 76m) | ThermaShield® Gloss 3mil | 62408 | 61" x 500' (1.55 x 152m) |
| Jet Guard® UV Gloss 10mil | 62123 | 38" x 250' (965mm x 76m) | ThermaShield® Gloss 3mil | 62409 | 38" x 25' (965mm x 7.6m) |
| Jet Guard® UV Gloss 10mil | 62124 | 43" x 250' (1.09 x 76m) | ThermaShield® Gloss 5mil | 62411 | 38" x 250' (965mm x 76m) |
| Jet Guard® UV Gloss 10mil | 62125 | 51" x 250' (1.29 x 76m) | ThermaShield® Gloss 5mil | 62415 | 43" x 250' (1.09 x 76m) |
| Jet Guard® UV Gloss 10mil | 62126 | 55" x 250' (1.40 x 76m) | ThermaShield® Gloss 5mil | 62412 | 51" x 250' (1.29 x 76m) |
| Jet Guard® UV Gloss 10mil | 62127 | 61" x 250' (1.55 x 76m) | ThermaShield® Gloss 5mil | 62413 | 61" x 250' (1.55 x 76m) |
| Jet Guard® UV Gloss 10mil | 62121 | 38" x 25' (965mm x 7.6m) | ThermaShield® Gloss 5mil | 62414 | 38" x 25' (965mm x 7.6m) |
| Jet Guard® UV Luster 3mil | 62132 | 25" x 250' (635mm x 76m) | ThermaShield® Gloss 10mil | 62416 | 38" x 250' (965mm x 76m) |
| Jet Guard® UV Luster 3mil | 62133 | 38" x 250' (965mm x 76m) | ThermaShield® Gloss 10mil | 62420 | 43" x 250' (1.09 x 76m) |
| Jet Guard® UV Luster 3mil | 62134 | 43" x 250' (1.09 x 76m) | ThermaShield® Gloss 10mil | 62417 | 51" x 250' (1.29 x 76m) |
| Jet Guard® UV Luster 3mil | 62135 | 51" x 250' (1.29 x 76m) | ThermaShield® Gloss 10mil | 62418 | 61" x 250' (1.55 x 76m) |
| Jet Guard® UV Luster 3mil | 62136 | 55" x 250' (1.40 x 76m) | ThermaShield® Gloss 10mil | 62419 | 38" x 25' (965mm x 7.6m) |
| Jet Guard® UV Luster 3mil | 62137 | 61" x 250' (1.55 x 76m) | ThermaShield® Luster 3mil | 62421 | 38" x 500' (965mm x 152m) |
| Jet Guard® UV Luster 3mil | 62131 | 38" x 25' (965mm x 7.6m) | ThermaShield® Luster 3mil | 62425 | 43" x 500' (1.09 x 152m) |
| Jet Guard® UV Matte 3mil | 62142 | 25" x 250' (635mm x 76m) | ThermaShield® Luster 3mil | 62422 | 51" x 500' (1.29 x 152m) |
| Jet Guard® UV Matte 3mil | 62143 | 38" x 250' (965mm x 76m) | ThermaShield® Luster 3mil | 62423 | 61" x 500' (1.55 x 152m) |
| Jet Guard® UV Matte 3mil | 62144 | 43" x 250' (1.09 x 76m) | ThermaShield® Luster 3mil | 62424 | 38" x 25' (965mm x 7.6m) |
| Jet Guard® UV Matte 3mil | 62145 | 51" x 250' (1.29 x 76m) | ThermaShield® Matte 3mil | 62426 | 38" x 500' (965mm x 152m) |
| Jet Guard® UV Matte 3mil | 62146 | 55" x 250' (1.40 x 76m) | ThermaShield® Matte 3mil | 62430 | 43" x 500' (1.09 x 152m) |
| Jet Guard® UV Matte 3mil | 62147 | 61" x 250' (1.55 x 76m) | ThermaShield® Matte 3mil | 62427 | 51" x 500' (1.29 x 152m) |
| Jet Guard® UV Matte 3mil | 62141 | 38" x 25' (965mm x 7.6m) | ThermaShield® Matte 3mil | 62428 | 61" x 500' (1.55 x 152m) |
| | | | ThermaShield® Matte 3mil | 62429 | 38" x 25' (965mm x 7.6m) |

Technical Specifications

| | Jet Guard® UV Gloss | Jet Guard® UV Luster | Jet Guard® UV Matte | Jet Guard® Deep Crystal® | Jet Guard® Crystal® Matte | ThermaShield® Gloss | ThermaShield® Luster | ThermaShield® Matte |
|------------------------|-------------------------------------|---------------------------------|---------------------------------|---------------------------------|---------------------------------|--------------------------------------------------|---------------------------------|---------------------------------|
| Film Type | Polyester | Polyester | Polyester | Polyester Base | Polyester Base | Polyester | Polyester | Polyester |
| Adhesive Type | Extruded Copolymer ¹ | Extruded Copolymer ¹ | Extruded Copolymer ¹ | Extruded Copolymer ¹ | Extruded Copolymer ¹ | Extruded Copolymer ¹ | Extruded Copolymer ¹ | Extruded Copolymer ¹ |
| Thickness | 3.0 mil 5.0 mil 10.0 mil | 3.0 mil | 3.0 mil | 6.0 mil | 6.0 mil | 1.7 mil 3.0 mil 5.0 mil 10.0 mil | 3.0 mil | 3.0 mil |
| Film/Adhesive Ratio | 1.0 / 2.0 3.0 / 2.0 7.0 / 3.0 | 1.0 / 2.0 | 1.0 / 2.0 | 3.4 / 2.6 | 3.4 / 2.6 | 0.5 / 1.2 1.0 / 2.0 2.0 / 3.0 4.0 / 6.0 | 0.5 / 2.5 | 0.5 / 2.5 |
| Activation Temperature | 185-205°F (85-96°C) | 185-205°F (85-96°C) | 185-205°F (85-96°C) | 185-205°F (85-96°C) | 185-205°F (85-96°C) | 220-235°F (104-112°C) | 220-235°F (104-112°C) | 220-235°F (104-112°C) |
| UV Absorbers | YES | YES | YES | NO | NO | NO | NO | NO |

¹ Extruded Copolymer adhesive formulations

Contact your local distributor:



Seal Graphics Americas Corporation
7091 Troy Hill Drive
Elkridge, MD 21075
Tel: 410-379-5400
Fax: 410-579-8960

Seal Graphics Canada
1601 Matheson Blvd. E.
Mississauga, Ontario
Canada, L4W 1H9
Tel: 905-212-9232
Fax: 905-212-9313