





TEXWALK[™]

14 Mil Opaque Textured Floor/Wall Vinyl Media

Product Description

TexWalk is an 14 mil opaque textured floor/wall vinyl material with fabric backing and repositionable, solvent acrylic adhesive. TexWalk works on carpet, tile, wood, metal and painted surfaces. TexWalk is printable via UV, Latex, solvent or eco-solvent inks.

SPECIFICATIONS Physical properties***

- Basis Weight 14 Mil
- ASTM D-2047 Certified ****Target Values

Features

- Structured matte finish
- Little to no adhesive residue
- Sticks on almost any surface
- Easy to apply and remove
- Print and go—no laminate solution

Recommended Storage Conditions and Shelf Life

- It is recommended to store the product in closed packaging at a temperature of +60°F to +85°F (+15°C to +30°C) and humidity range of 45% to 60%.
- The product has a shelf life of 24 months.

Environmental, Health & Safety

- No Material Safety Data Sheet required.
- Waste is not suitable for recycling.

Main Applications

- POP-Point-of-Purchase
- Tradeshows (Walls and Floors)
- Indoor Wall Graphics
- Door Coverage
- Apply on carpeting and tiles

Printer/Ink Compatibility

TexWalk is printable on UV-curable, Latex, eco-solvent and solvent inkjet printers. Application surface must be dry, clean and above 50° before application.

Application Instructions

Please refer to the Application guide which you can download off the website: www.asphaltartusa.com

Durability

TexWalk will last up to 1 month on indoor floor applications, depending on the type of traffic. Indoor wall applications will last up to 24 months.



OCÉ UV CURABLE, LATEX, AND DISPLAY GRAPHICS MEDIA SUPPLIES

Selected Available Roll Sizes

ITEM NUMBER	WIDTH X LENGTH	QTY. PER CARTON	CORE
TXWALK2310	23" x 10'	1 Roll	3"
TXWALK4882	48" x 62'	1 Roll	3"





CANON SOLUTIONS AMERICA

OCÉ IMAGING SUPPLIES 100 PARK BLVD., ITASCA, IL 60143

P: 1-800-323-4827 | F: 1-800-351-0085 ocesuppliesoc@csa.canon.com

CSA.CANON.COM